

Custom designed units to Client specification

Technical data: Standard unit

Description: S3 Combo unit (STD)

- 1 7M Seven Steel Filter (7 Meters of Ceramic)
- 2 Auto coalesce two stage Water Separator
 - 1 Water trap - Tray (optional)
 - 2 Water trap - Cage (optional)
- 1 Combo Stand

All fully connected with single inlet /outlet

Part no: S3

Flow Rate Max: 300 ltr/pm

Micron Rating: 1, 5, 10, 15 elements

Diesel Vol.: 321 ltr

Mass Vol: 515 kg

Mass Empty: 259 kg

Height 1340 mm

Length: 1350 mm

Width 1400 mm

Port size STD 1 ½ inch

Pipe fitted – hydraulic 1 inch

Valves 2

Max pressure 4 Bar

Gauges 2

Clean pressure drop 0.2 Bar

Mini mesh sample 2

The unit is highly effective in dealing with particle and high free water contamination on a sustainable basis.

Use usually in conjunction with additional bag filters e.g. S5 skid (Four bag filters) .With easy installation and low maintenance required.

The unit allows five stage filtration. This is required for effective, sustainable cleanliness levels in any filtration system, especially in Africa. Providing unsurpassed sustainable cleanliness levels at bulk tanks

